

Solco Flexi Tape

Description:

Solco Flexi Tape is a synthetic butyl/rubber based reinforced sealant strip used mainly in conjunction with Solco DPM & Liquid Gas Barrier Systems.

It is also an excellent accessory for use with Solco liquid applied membrane offering a simple method for waterproofing building materials prior to finishing.

Solco Flexi-Tape can be used to protect most building surfaces from the effect of liquid and water vapour. It is flexible enough to take up any movement encountered within the substrates to which it is applied. It also has the potential to bridge cracks of up to 2 mm.

Application:

Solco Flexi-Tape is a fleece covered membrane roll used in conjunction with Solco Liquid DPM & Gas Barrier. It is specifically designed for use as reinforcement at high stress points in areas such as floor/wall juncture and joints.

The Flexi-Tape is bedded in to the wet first coat once tacky and is over-coated with a second coat of Solco DPM & Liquid Gas Barrier, this ensures continuity and integrity of the system.

Colour: Grey

Roll Size: 2 mm x 100 mm x 5 m

Tolerance: Thickness + 0.2 mm, width 2 mm

Service Temperature Range: -40°C to +90C

Preparation & Application:

All surfaces must be thoroughly clean, dry and free from frost, grease and loose materials.

The Solco Flexi-Tape is bedded in to the wet first coat, and once tacky, is over-coated with a second wet coat.

Packaging:

Supplied as a single roll 5 m length.



- Water Based
- Low VOC's
- Flexible for uneven surfaces
- Waterproof membrane
- Use in conjunction with Solseal Liquid Gas Membrane

Storage: Above ground in dry conditions.

Shelf Life: 12 months unopened.

This product is classified as non hazardous