

SOLCEM

Solcure Sealer PF

Concrete Curing & Sealing Compound for Power Floated Floors

DESCRIPTION

A clear acrylic polymer resin solution primarily for application to surfaces of freshly laid concrete floors that have been power float finished. Initially Solcure Sealer PF will form a highly effective curing membrane that conforms to ASTM. C309 and secondly will act as an in-depth sealer for the hardened concrete rendering its surface dustproof and extremely hard wearing.

- Easily applied by spray, single coat application.
- 75% Curing efficiency.
- Cures & Seals in one operation.

Colour	Product Code	Size
Colourless	SOLCURESEALERPF25	25 litres
	SOLCURESEALERPF210	210 litres

TYPICAL USES

- Solcure Sealer PF is used for curing, sealing and dustproofing concrete which has been power float finished.
- Solcure Sealer PF provides abrasion resistant hard wearing easy-clean surface.

FEATURES & BENEFITS

- Cures and seals in one operation saving time and labour.
- Ideal for use in fast-track construction.
- Curing efficiency 75% in accordance with ASTM. C309.
- Provides abrasion resistant hard wearing easy-clean surface.
- Effective anti-carbonation coating.
- Permits bond of most subsequent coatings intended for concrete.

APPLICATION

- Apply by fan-jet sprayer to achieve a typical coverage of 12 m² per litre immediately after final finishing and when surface water is no longer evident.
- Avoid over application, Solcure Sealer PF should not be allowed to form 'puddles' but to just leave a wet gloss appearance.

SPRAYER CLEANING

Immediately after spraying, clean line and nozzle thoroughly with white spirit. If not possible to carry out immediately, or if sprayer has been standing, clean with Solklens

OVERCOATING

In general most paints and cement grouts will adhere well to concrete treated with Solcure Sealer PF, but to ensure compatibility it is advisable to first apply a test patch.

COVERAGE

New concrete 12 square metres per litre will generally be sufficient. Coverage will vary depending on surface porosity and texture.

STORAGE

Keep containers sealed. Store in dry conditions at room temperature and away from direct heat. All applicable storage requirements for flammable materials should be observed.

SHELF LIFE

1 year in sealed container.

TECHNICAL DATA

Drying time - Touch Dry	2-4 hours
Drying time - Hard Dry	18-24 hours
Curing Efficiency	75%
Coverage	12m ² / Litre
Flash Point	40°C

HEALTH & SAFETY

Solcure Sealer PF is flammable. Avoid physical contact with material and inhalation. If contact with skin should occur wash with a suitable antiseptic cleaner and then soap and water. If splashes should affect eyes, bathe immediately with copious quantities of clean water and then immediately seek medical advice.