



SAFETY DATA SHEET

SOLCURE SEALER

Page: 1

Compilation date: 19/05/2016

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: SOLCURE SEALER

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC15: Non-metal-surface treatment products.

1.3. Details of the supplier of the safety data sheet

Company name: Solco
Unit 51
Portmanmoor Road Ind Est
Ocean Park
Cardiff
CF24 5HB
United Kingdom

Tel: 02920 495 555

Fax: 02920 491 700

Email: enquiries@solco.co.uk

1.4. Emergency telephone number

Emergency tel: 02920 495 555
(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Flam. Liq. 3: H226; Aquatic Chronic 2: H411; Skin Irrit. 2: H315; Acute Tox. 4: H312; Acute Tox. 4: H332; STOT SE 3: H336; Asp. Tox. 1: H304; Eye Irrit. 2: H319

Most important adverse effects: Flammable liquid and vapour. May be fatal if swallowed and enters airways. Harmful in contact with skin. Causes skin irritation. Harmful if inhaled. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H226: Flammable liquid and vapour.
H304: May be fatal if swallowed and enters airways.
H312: Harmful in contact with skin.
H315: Causes skin irritation.
H332: Harmful if inhaled.
H336: May cause drowsiness or dizziness.
H411: Toxic to aquatic life with long lasting effects.

[cont...]

SAFETY DATA SHEET

SOLCURE SEALER

Page: 2

Hazard pictograms: GHS07: Exclamation mark

GHS02: Flame

GHS08: Health hazard

GHS09: Environmental



Signal words: Danger

Precautionary statements: P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233: Keep container tightly closed.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P241: Use explosion-proof electrical/ventilating/lighting equipment.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P304+341: IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

P331: Do NOT induce vomiting.

P405: Store locked up.

P501: Dispose of contents/container to registered waste disposal centre.

2.3. Other hazards

Other hazards: Flammable. Harmful in contact with skin. Harmful by inhalation.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Non-classified ingredients:

XYLENE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
215-535-7	1330-20-7	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	10-30%

[cont...]

SAFETY DATA SHEET

SOLCURE SEALER

Page: 3

KEROSENE - UNSPECIFIED - KEROSENE (PETROLEUM), HYDRODESULPHURIZED - REACH registered number (s): 01-2119485517-27-XXXX

232-366-4	8008-20-6	-	Asp. Tox. 1: H304; Aquatic Chronic 2: H411; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H336	50-70%
-----------	-----------	---	--	--------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water. Remove all contaminated clothes and footwear immediately unless stuck to skin.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. Wash out mouth with water. If conscious, give half a litre of water to drink immediately. Give 1 cup of water to drink every 10 minutes. If unconscious and breathing is OK, place in the recovery position. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Move to fresh air in case of accidental inhalation of vapours. If conscious, ensure the casualty sits or lies down. If unconscious and breathing is OK, place in the recovery position. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact:

There may be irritation and redness at the site of contact. An itchy rash may occur at the site of contact.

There may be irritation and redness.

Eye contact:

There may be soreness and redness of the mouth and throat. There may be vomiting and diarrhoea. The breathing may become shallow and rapid.

Ingestion:

There may be a feeling of tightness in the chest with shortness of breath. There may be congestion of the lungs causing severe shortness of breath. Drowsiness or mental confusion may occur. There may be loss of consciousness.

Inhalation:

Immediate effects can be expected after short-term exposure. There may be vomiting and diarrhoea. Breathing may stop.

Delayed / immediate effects:

4.3. Indication of any immediate medical attention and special treatment needed

Show this safety data sheet to the doctor in attendance. In case of shortness of breath, give oxygen. Eye bathing equipment should be available on the premises. A decontamination shower should be available on the premises.

Immediate / special treatment:

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Carbon dioxide. Dry chemical powder. Alcohol or polymer foam. Water fog.

[cont...]

SAFETY DATA SHEET

SOLCURE SEALER

Page: 4

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Highly flammable. Harmful. Vapour may travel considerable distance to source of ignition and flash back. In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Eliminate all sources of ignition. Turn leaking containers leak-side up to prevent the escape of liquid. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding. Alert the neighbourhood to the presence of fumes or gas.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Mix with sand or vermiculite. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Earth any equipment used in handling. Smoking is forbidden. Use non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep away from sources of ignition. Keep container tightly closed. Keep away from direct sunlight. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition. Ensure storage room has retention walls. The floor of the storage room must be impermeable to prevent the escape of liquids.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): PC15: Non-metal-surface treatment products.

[cont...]

SAFETY DATA SHEET

SOLCURE SEALER

Page: 5

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	220 mg/m ³	441 mg/m ³	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition. Ensure storage room has retention walls. The floor of the storage room must be impermeable to prevent the escape of liquids.

Respiratory protection: Gas/vapour filter, type A: organic vapours (EN141). Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Gloves (solvent-resistant).

Eye protection: Safety glasses with side-shields. Safety goggles.

Skin protection: Solvent resistant protective clothing. PVC apron.

Environmental: Ensure storage room has retention walls. The floor of the storage room must be impermeable to prevent the escape of liquids. Prevent from entering in public sewers or the immediate environment. Ensure emissions from ventilation or equipment comply with environmental protection legislation.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Off-white

Odour: Aromatic

Evaporation rate: Moderate

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Viscosity: Non-viscous

Boiling point/range°C: 136-144

Melting point/range°C: Not applicable.

Flammability limits %: lower: No data available.

upper: No data available.

Flash point°C: <23

Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available.

Vapour pressure: No data available.

Relative density: 0.824@15.6C

pH: Not applicable.

VOC g/l: No data available.

[cont...]

SAFETY DATA SHEET

SOLCURE SEALER

Page: 6

9.2. Other information

Other information: Not applicable.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Not applicable.

10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Not applicable.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Section 11: Toxicological information

11.1. Information on toxicological effects

Relevant hazards for product:

Hazard	Route	Basis
Acute toxicity (ac. tox. 4)	INH DRM	Hazardous: calculated
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated
Aspiration hazard	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact. An itchy rash may occur at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat. There may be vomiting and diarrhoea. The breathing may become shallow and rapid.

Inhalation: There may be a feeling of tightness in the chest with shortness of breath. There may be congestion of the lungs causing severe shortness of breath. Drowsiness or mental confusion may occur. There may be loss of consciousness.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure. There may be vomiting and diarrhoea. Breathing may stop.

[cont...]

SAFETY DATA SHEET

SOLCURE SEALER

Page: 7

Other information: Not applicable.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values:

Species	Test	Value	Units
RAINBOW TROUT (<i>Oncorhynchus mykiss</i>)	96H LC50	7.6	mg/l
Daphnia magna	48H EC50	3.82	mg/l
ALGAE	48H EC50	4.36	mg/l

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: Slightly bioaccumulable.

12.4. Mobility in soil

Mobility: Volatile. Floats on water. Insoluble in water. Absorbed only slowly into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: 1223(main component)

14.2. UN proper shipping name

Shipping name: Mixture of hydrocarbon solvents
(KEROSENE - UNSPECIFIED - KEROSENE (PETROLEUM), HYDRODESULPHURIZED;
HYDROCARBONS C9-12, N-ALKANES, ISOALKANES, CYCLIC AROMATICS (2-25%);
XYLENE)

14.3. Transport hazard class(es)

Transport class: 3

[cont...]

SAFETY DATA SHEET

SOLCURE SEALER

Page: 8

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: Yes

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H332: Harmful if inhaled.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.