

# Solco Single Sided DPM Joint Tape

## Description:

Solco Single Sided DPM Joint Tape is an extra strong Cross-weave fiberglass filament reinforced clear BOPP tape. The tape is coated with a synthetic rubber and hydrocarbon resin adhesive. The reinforced tape is tear-resistant and has a very strong adhesion and tack to damp proof membranes.

## Applications:

Solco Single Sided DPM Joint Tape is suitable for sealing Damp Proof Membranes including HP Performance DPM's & Attenuation Membranes at overlaps. Use in conjunction with Solco D/S Butyl Tape which is used to bond two membranes together & then over-seal with the Solco DPM Tape. It can also be used around pipe penetrations & as a patch when membranes become punctured.

## Installation:

- Ensure that surfaces are clean and dry.
- Apply tape equidistant over the bonded membrane lap.
- Apply pressure to the tape to ensure adhesion.
- When the weather is cold, store tape in a warm, dry place until required. Installation is not recommended below 5°C.

## Tech Data:

Description	Units	Value	Test Method
Total thickness	mic	120	Digital calliper
Peel adhesion	N/cm	10	AFERA
Elongation at break	%	5	AFERA
Tensile strength	N/cm	240	AFERA



## Roll Sizes

75mm wide x 25mt long

## Declaration of Conformity:

**BS EN8485+A1:2019:** Code of practice for the design of protective measures for methane and carbon dioxide ground gases for new buildings - ISO 15105.

## REACH SVHC Status:

NO SVHC present according to candidates list of the UK 25/06/20 & EU 17/01/23

## Storage:

Recommended shelf life of 12 months from date of despatch at the moderate temperature and humidity environment.

Solco, Unit 51, Portmanmoor Road Industrial Estate, Ocean Park, Cardiff, CF24 5HB