SOLCO

SAFETY DATA SHEET

SOLWAX

Page: 1

Compilation date: 17/09/2018

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: SOLWAX

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC24: Lubricants, greases, release products. Concrete Release Agent

1.3. Details of the supplier of the safety data sheet

Company name: Solco

Unit 51

Portmanmoor Road Ind Est

Ocean Park
Cardiff
CF24 5HB
United Kingdom

Tel: 02920 495 555
Fax: 02920 491 700

Email: enquiries@solco.co.uk

1.4. Emergency telephone number

Emergency tel: 02920 495 555

(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Asp. Tox. 1: H304

Most important adverse effects: May be fatal if swallowed and enters airways.

2.2. Label elements

Label elements:

Hazard statements: H304: May be fatal if swallowed and enters airways.

Hazard pictograms: GHS08: Health hazard



Signal words: Warning

Precautionary statements: P281: Use personal protective equipment as required.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P302+P350: IF ON SKIN: Gently wash with plenty of soap and water.

SOLWAX

Page: 2

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P306+P360: IF ON CLOTHING: rinse immediately contaminated clothing and skin with plenty of water before removing clothes.

P331: Do NOT induce vomiting.

P402+P404: Store in a dry place. Store in a closed container.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

BASEOIL - UNSPECIFIED - DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC - REACH registered number(s): 01-2119480375-34-0010

EINECS	CAS	PBT / WEL	CLP Classification	Percent
265-156-6	64742-53-6	Substance with a Community	-	70-90%
		workplace exposure limit.		

Contains: A blend of hydrocarbon waxes and highly refined minerals. The mixture is a solid paste despite the huge quantity of hydrocarbon solvent. This is due to the liquid having been absorbed by the blend of waxes.

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water

to drink immediately. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to

hospital as soon as possible.

Inhalation: Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

There may be irritation of the throat. Ingestion:

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: No effects can be expected after short term exposure.

[cont...]

SOLWAX

Page: 3

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a suitable container.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: Respirable dust

State 8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
------------------	--------------	------------	--------------

SOLWAX

Page: 4

EU 5mg/m3 10mg/m3	-
-------------------	---

DNEL/PNEC Values

SOLWAX

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	5.4mg/m3	Workers	Local

Hazardous ingredients:

BASEOIL - UNSPECIFIED - DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	5.4mg/m³/8h	-	-
PNEC	Oral-secondary poisoning	9.33 mg/kg	-	-

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: Prevent from entering in public sewers or the immediate environment.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Wax

Colour: Green-blue

Odour: Characteristic odour

Evaporation rate: Not applicable.

Oxidising: Not applicable.

Solubility in water: Insoluble

Viscosity: Viscous

Boiling point/range°C: >350 Flash point°C: >150

pH: NA

9.2. Other information

Other information: Not applicable.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

SOLWAX

Page: 5

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values:

Route	Species	Test	Value	Units
DERMAL	RAT	LD50	>2000	mg/kg
VAPOURS	RAT	4H LD50	>5	mg/l
ORAL	RAT	LD50	>5000	mg/kg

Hazardous ingredients:

BASEOIL - UNSPECIFIED - DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC

DERMAL	RAT	LD50	>5000	mg/kg
DUST/MIST	RAT	LC50	>5	mg/l/8h
ORAL	RAT	LD50	>5000	ma/ka

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: No effects can be expected after short term exposure.

Other information: Not applicable.

Section 12: Ecological information

12.1. Toxicity

SOLWAX

Page: 6

Ecotoxicity values:

Species	Test	Value	Units
MYSID SHRIMP (Mysidopsis bahia)	96H LC50	>500,000	ppm
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	>400,000	ppm

Hazardous ingredients:

BASEOIL - UNSPECIFIED - DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC

ALGAE	48H IC50	100	mg/l
Daphnia magna	48H EC50	10,000	mg/l
FISH	96H LC50	100	mg/l

12.2. Persistence and degradability

Persistence and degradability: Not readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

Recovery operations: Not applicable.

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

SOLWAX

Page: 7

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H304: May be fatal if swallowed and enters airways.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.