

SOLSTRIKE

Page: 1

[cont...]

Compilation date: 23/09/2021

Revision No: 1

### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: SOLSTRIKE

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC24: Lubricants, greases, release products.

## 1.3. Details of the supplier of the safety data sheet

Company name: Solco

Unit 51

Portmanmoor Road Ind Est

Ocean Park
Cardiff
CF24 5HB

United Kingdom

**Tel:** 02920 495 555 **Fax:** 02920 491 700

Email: enquiries@solco.co.uk

# 1.4. Emergency telephone number

**Emergency tel:** 02920 495 555

(office hours only)

#### Section 2: Hazards identification

## 2.1. Classification of the substance or mixture

Classification under CLP: Asp. Tox. 1: H304; Skin Irrit. 2: H315; Acute Tox. 4: H332; STOT SE 3: H336; Aquatic

Chronic 2: H411

Most important adverse effects: May be fatal if swallowed and enters airways. Causes skin irritation. Harmful if inhaled.

May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.

## 2.2. Label elements

## Label elements:

**Hazard statements:** H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation. H332: Harmful if inhaled.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

Hazard pictograms: GHS07: Exclamation mark

GHS08: Health hazard

GHS09: Environmental

**SOLSTRIKE** 









Signal words: Danger

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P240: Ground and bond container and receiving equipment.

P241: Use explosion-proof electrical/ventilating/lighting/... equipment.

P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P280: Wear protective gloves/protective clothing/eye protection/face protection. P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P302+P352: IF ON SKIN: Wash with plenty of water.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water.

P331: Do NOT induce vomiting.

P405: Store locked up.

P501: Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

#### 2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

#### 3.2. Mixtures

#### Hazardous ingredients:

BASEOIL - UNSPECIFIED - DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC - REACH registered number(s): 01-2119480375-34-0010

EINECS	CAS	PBT / WEL	CLP Classification	Percent
265-156-6	64742-53-6	Substance with a Community	-	70-90%
		workplace exposure limit.		

# STRAIGHT RUN KEROSINE - KEROSINE (PETROLEUM)

232-366-4 8008-20-6	-	Asp. Tox. 1: H304	10-30%	
---------------------	---	-------------------	--------	--

# Section 4: First aid measures

#### 4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water. Do not induce vomiting. Transfer to hospital as soon as

possible.

[cont...]

SOLSTRIKE

Page: 3

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

## 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat. There may be difficulty

swallowing. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: Absorption through the lungs can occur causing symptoms similar to those of ingestion.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

## 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

## Section 5: Fire-fighting measures

## 5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

#### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes. Harmful.

# 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

## Section 6: Accidental release measures

# 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Mark out the contaminated area

with signs and prevent access to unauthorised personnel. Turn leaking containers

leak-side up to prevent the escape of liquid.

# 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

# 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method. Do not use equipment in clean-up procedure which

may produce sparks.

## 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

#### **SOLSTRIKE**

Page: 4

# Section 7: Handling and storage

## 7.1. Precautions for safe handling

Handling requirements: Smoking is forbidden. Use non-sparking tools. Ensure there is sufficient ventilation of

the area. Avoid the formation or spread of mists in the air.

# 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from

sources of ignition. Prevent the build up of electrostatic charge in the immediate area.

Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Steel drums. Polyethylene.

## 7.3. Specific end use(s)

Specific end use(s): No data available.

## Section 8: Exposure controls/personal protection

#### 8.1. Control parameters

#### Workplace exposure limits:

#### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	200 mg/m³	-	-	-

## Hazardous ingredients:

# BASEOIL - UNSPECIFIED - DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC

## Workplace exposure limits:

#### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
EU	5 mg/m³	10 mg/m³	-	-

## **DNEL/PNEC Values**

#### **SOLSTRIKE**

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	-	-	-
PNEC	Oral	9.33	-	-

# Hazardous ingredients:

## BASEOIL - UNSPECIFIED - DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC

Тур	е	Exposure	Value	Population	Effect
DNE	iL	Inhalation	5.4mg/m³/8h	-	-

#### SOLSTRIKE

Page: 5

PNEC	Oral-secondary poisoning	9.33 mg/kg	-	-	
------	--------------------------	------------	---	---	--

#### 8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical

equipment are not a source of ignition.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: Prevent from entering in public sewers or the immediate environment. The floor of the

storage room must be impermeable to prevent the escape of liquids. Ensure storage

room has retention walls.

# Section 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Amber

Odour: Hydrocarbon

Solubility in water: Insoluble

Viscosity: Non-viscous

Kinematic viscosity: 2.8

Viscosity test method: Kinematic viscosity in 10-6 m2/s at 40°C (ISO 3104/3105)

Boiling point/range°C: 140 - 300 Melting point/range°C: No data available.

Flammability limits %: lower: No data available. upper: No data available.

Flash point°C: > 65 Part.coeff. n-octanol/water: No data available.

Autoflammability°C: 250 Vapour pressure: No data available.

**Relative density:** 0.83-0.86 @ 15.6°C **pH:** No data available.

VOC g/I: No data available.

## 9.2. Other information

Other information: Not applicable.

## Section 10: Stability and reactivity

# 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

# 10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

## 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

**SOLSTRIKE** 

Page: 6

#### 10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

# 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

#### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

## Section 11: Toxicological information

## 11.1. Information on toxicological effects

## **Toxicity values:**

Route	Species	Test	Value	Units
DERMAL	RBT	LD	>2000	mg/kg
VAPOURS	RAT	4H LC	>5.2	mg/l
ORAL	RAT	LD50	>5000	mg/kg

## **Hazardous ingredients:**

## BASEOIL - UNSPECIFIED - DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC

DERMAL	RAT	LD50	>5000	mg/kg
DUST/MIST	RAT	LC50	>5	mg/l/8h
ORAL	RAT	LD50	>5000	mg/kg

# STRAIGHT RUN KEROSINE - KEROSINE (PETROLEUM)

IPR	RAT	LDLO	10700	mg/kg
IPR	RBT	LD50	6600	mg/kg
ORL	RBT	LD50	2835	mg/kg

#### Relevant hazards for product:

Hazard	Route	Basis
Acute toxicity (ac. tox. 4)	INH	Hazardous: calculated
Skin corrosion/irritation	DRM	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated
Aspiration hazard	-	Hazardous: calculated

## Symptoms / routes of exposure

**Skin contact:** There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat. There may be difficulty

swallowing. Nausea and stomach pain may occur. There may be vomiting.

SOLSTRIKE

Page: 7

Inhalation: Absorption through the lungs can occur causing symptoms similar to those of ingestion.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

Other information: Not applicable.

## **Section 12: Ecological information**

#### 12.1. Toxicity

#### Hazardous ingredients:

# BASEOIL - UNSPECIFIED - DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC

ALGAE	48H IC50	100	mg/l
Daphnia magna	48H EC50	10,000	mg/l
FISH	96H LC50	100	mg/l

## 12.2. Persistence and degradability

Persistence and degradability: No data available.

#### 12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

#### 12.4. Mobility in soil

Mobility: Readily absorbed into soil.

#### 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

## 12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms.

#### Section 13: Disposal considerations

## 13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

Recovery operations: Not applicable.

**Disposal of packaging:** Arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

#### **Section 14: Transport information**

Transport class: This product does not require a classification for transport.

#### Section 15: Regulatory information

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

SOLSTRIKE

Page: 8

## 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

## **Section 16: Other information**

#### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

**Phrases used in s.2 and s.3:** H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H332: Harmful if inhaled.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.